Full Speed to Go ,
Full Power to Last

Anker SOLIX C1000 Portable Power Station

1056Wh | 1800W



InfiniPower™ GaNPrime™

HYPER FLASH TotalGuard™ SurgePad™

Highlights

InfiniPower™ 10 Years of Everyday Use

LiFePO4 batteries offer a 6× longer lifespan than the average power station. Designed for a decade of daily use, with an industry-leading 5-year device warranty

HyperFlash™ Fast Recharge

You don't have a second to waste. Whether you've got a big trip or bad weather is on the horizon, Anker SOLIX C1000 recharges to 100% in just 58 minutes.* That's 27.5% faster than power stations with the same capacity for ultra-fast, worry-free recharging.

Power Anything with SurgePad™ Technology

Sip on freshly brewed coffee and grill up breakfast at the same time. With SurgePad™ Technology, You have up to 2400W output that powers 99% of appliances.



Features

Proven Durability TotalGuard™

Our drop-proof design and material selection meet the requirements of industry testing standards to withstand any impact during outdoor adventures.

Pro UPS

Ensure continuous power with Uninterruptible Power Supply (UPS) Switchover time in under 20ms.

15% Smaller Than Industry Average

You don't need to do any heavy lifting. Anker SOLIX C1000 is more compact and just as powerful as similar-capacity LFP power stations.

Flat Top for Extra Space

Give yourself some extra room thanks to the flat design of Anker SOLIX C1000. You can set your devices or batteries on top, just like a desk.

Specifications

Product Model

PN	A1761
Model Name	Anker SOLIX C1000 Portable Power Station

Battery Info

Type of Battery	LiFePO4
Capacity	1056Wh
Capacity	330000mAh
Cycle Life	3000+ (to 80%)



Especificaciones técnicas

Central eléctrica portátil C1000

Capacidad:	**1056 Wh**
Tipo de batería:	**LiFePO4 (fosfato de hierro y litio)**
Ciclos de vida de la batería:	**3.000 (80% de capacidad)**
Salida continua de CA:	**Onda sinusoidal pura de 1800 W**
Salida de sobretensión de CA:	**2400 W**
Tomas de corriente CA:	**6×**
Recarga de entrada solar:	**600 W máx., MPPT de 11-60 V**
Recarga de entrada de CA:	**1.300 W máx.**
Salida del encendedor de cigarrillos:	**120 W, 12 V/10 A**
Tiempo de conmutación del SAI:	**<20 ms**
Salida USB-A:	**2×12 W**
Salida USB-C:	**1×100 W, 1×30 W**
Escalabilidad:	**Hasta un máximo de 2112 Wh de capacidad con batería de expansión (próximamente).**
Temperatura de descarga:	**-4 °F - 104 °F**
Temperatura de carga:	**32 °F - 104 °F**
Conexión inalámbrica para la aplicación	**Wi-Fi y Bluetooth**
Largo x Ancho x Alto	**14,8 × 8,07 × 10,5 pulgadas 37,6 × 20,5 × 26,7 cm**
Peso neto:	**28,44 libras/12,9 kg**

ANKER SOLIX

Specifications

Power Inputs

Input Votage	100-120V (US/CA/JP) 220-240V (UK/EU/MEA/CN/AU)
Total Input Power	1300W (AC Direct)
EST Recharge Time	Default AC recharging: 90min(1000W) Ultra Fast AC recharging: 58min(1300W) Car socket recharging: 10.7h(120W) solar recharging: 1.8h(600W)
Use Ports While Recharging	Yes
Direct AC Input	Yes
Maximum AC Input Power	1300W
# of DC Input	1
DC Adapter	No
DC Adapter Input Power	-
EST DC Adapter Recharge Time	10.7 hrs (120W Car Charger)
DC Input Size	XT-60
Solar Input Power	11-32V⎓ 10A; 32V-60V⎓ 12.5A (600W Max)
EST Solar Recharge Time	6.1 Hours (2*100W) 4 Hours(3*100W) 3.6 Hours(2*200W) 2 Hours(3*200W) 1.8 Hours (2*400W)
Solar Panel Compatible	Yes
MPPT Support	Yes

Sales Market: US/CA/JP/EU//UK/AU/TW/CN/MEA

Specifications

Illumination Information

Flash Light	-
Flash Light Mode	-
Ambient Light	Yes
Ambient Light Mode	Ambient Light Mode (3 Level) SOS Mode

Safety Information

Operation Temperature (°C/°F)	Charging: -20 -40°C / -4 -104°F Recharging: 0-40°C / 32-104°F
Overload Protection (AC)	>1800W
Over-current Protection (USB-A)	>2.4A
Over-current Protection (USB-C)	>3.6A (30W) >6A (100W)
Over-current Protection (Car port)	>10A

Package Content

AC Adapter	-
Cable	AC Charging Cable 150cm Car Charging Cable 300cm Solar Charging Cable (1 to 2) 170cm

Weight & Dimension

Product Dimension (mm)	376x205x267 mm
Packaging Dimension	Packaging 451x274x310mm UN BOX 464x287x330mm
Product Weight	12.9 kg ; 28.44 lb
Product Weight with Package	14.1 kg ; 31.09 lb