





This series can be defined as a phenomenon of adaptability to all rolling shutters balanced with compensation springs thanks to a continues improvement of the functional characteristics of the motors and their innovative design. We produce two versions of the motor Uniko: the single -head and the double-head model.

jer (in (in 199

UNIKO - 1M EVOLUTION - cod. 72110000 Single-head central motor for rolling shutters

UNIKO - 2M EVOLUTION - cod. 72210000 Double-head central motor for rolling shutters

Technical characteristics

	Model	Ø rolling shutter tube mm	Ø winding flange mm		Amperage A	% Services	Voltage V	Frequency Hz	Insulation Class	Capacitor in mF	R.P.M.	Torque Nm	Lifting capacity Kg
	UNIKO - 1M EVOLUTION	42* - 48* 60	200	450	2	90	230	50	F	16	9	177	180
			220**										170
	UNIKO - 2M EVOLUTION	42* - 48* 60	200	700	3	110	230	50	F	20	9	196	200
			220**										183

* with tube adaptor ** with flange adaptor

Accessories



Electromagnetic brake Cable 4 meters cod. 75130000



Brake release handle cod. 75160000



Kit flange adaptor Uniko from Ø 200mm to Ø 220mm cod. 75270000

Kit flange adaptor Uniko from Ø 200mm to Ø 206mm cod. 75290000



Tube adaptor from Ø 60 mm to Ø 48mm cod. 75260000

Tube adaptor from Ø 60 mm to Ø 42mm cod. 75250000